

Printer Specifications

Printhead	
Print Technology	Thermal Transfer
Print Resolution (dpi)	300
Print Speed (mm/sec)	125 mm/sec
Max. Print Width (mm)	105.60 mm
Material	
Continuous rolls or fan-folded	Double sided heat shrinkable sleeves
Material thickness mm	0.055 - 1.2
weight g/m ²	60 - 300
Label Dimension Limits*	Max. Width: 106.00 mm Min. Width: 4.00 mm Max. Height: 1000 mm Min. Height: 5.00 mm
Limits for continuous material and flat pressed tubes* from 0.4 thick mm	Max. Width: 110 mm Min. Width: 3.5 mm
Limits for carrier material	Max. Width: 110 mm Min. Width: 25 mm
Media roll	Total diameter: up to 300 mm Core diameter: 38 - 100 mm Winding direction: preferred inside*
Dimensions of the printer	
Height x Width x Depth	395.00 mm x 248.00 mm x 554.00 mm
Weight	21
Operation data	
Power Supply	100 - 240 V ~50/60 Hz, PFC
Power consumption	Max. 300 W
Operating Temperature	10°C - 35°C
Operating Humidity	30-85% (non-condensing)
Approval/Compliance	CE, FCC class A, CB, CCC, UL

*Critical materials or applications need to be tested and released.

Monitoring	
Stop printing if	End of ribbon End of labels Printhead open
On the display	Data reception WLAN field intensity Ethernet state Used memory Temperature printhead Access to memory card Remaining quantity of ribbon Clock Date sheet Abc debug Input buffer
Fonts	
Font Types	5 Bitmap fonts incl. OCR-A, OCR-B and 3 Vector Swiss 721, Swiss 721 Bold and Monospace 821 available internally, loadable TrueType Fonts. Optional Chinese (simplified Chinese) Optional Thai
Character Sets	Windows 1250 up to 1257, DOS 437, 737, 775, 850, 852, 857, 862, 864, 866, 869, EBCDIC 500, ISO 8859-1 up to -10 and -13 up to -16, WinOEM 720, UTF-8, Macintosh Roman, DEC MCS, KOI8-R. All West and East European latin, cyrillic, greek, hebrew and arabic characters are supported. Optional Thai and Chinese.
Bitmap fonts	Size of width and height 1-3mm Zoom 2-10. Orientation 0°, 90°, 180°, 270°
Vector-/True Type fonts	Size of width and height 0.9 – 128 mm variable zoom Orientation 360° in steps of 1°
Font formats	–
Font width	Variable

Get a Full solution

Automated print & apply



Specialised high quality identification



Software



Support & services



www.bradyeurope.com/wire-automation



WHEN PERFORMANCE MATTERS MOST™

Brady EMEA Locations

Africa	+27 11 704 3295	Middle East	+971 4881 2524
Benelux	+32 (0) 52 45 78 11	Norway	+47 70 13 40 00
Central & Eastern Europe	+421 2 3300 4800	Romania	+40 21 202 3032
Denmark	+45 66 14 44 00	Russia	+7 495 269 47 87
France	+33 (0) 3 20 76 94 48	Spain & Portugal	+34 900 902 993
Germany	+49 (0) 6103 7598 660	Sweden, Finland, Baltic states	+46 (0) 8 590 057 30
Hungary	+36 23 500 275	Turkey	+90 212 264 02 20
Italy	+39 02 26 00 00 22	UK & Ireland	+44 (0) 1295 228 288

© 2019 Brady Worldwide Inc. All rights reserved.

Your Brady Distributor

www.bradyeurope.com

28/05/2019

EUR-O-604-EN