

BradyPrinter i3300 specifications

PRINTER	
Description	BradyPrinter i3300 Industrial Label Printer
Includes	This i3300 printer comes in a cardboard box. It ships with a power cord, a Brady Workstation Suite, a USB cable, a product CD holding the manual, a cleaning kit and a printed quick start guide
Applications	General & Industrial Identification; Circuit Board & Component Identification; Wire & Cable Marking; Laboratory Identification; Asset Identification; Workplace Safety & Compliance; Lean; 5S & Visual Workplace; Facility; Maintenance & Operations ID; Buildings & Grounds; Logistics/Warehousing
Print Speed (mm/sec)	101.60
Print Resolution (dpi)	300
Stand-alone Printing (Detached from PC)	Peripheral
Internal Memory	512 MB (RAM) - 195 MB (data storage)
Colour Capability	Monocolour
Language Support	Bulgarian, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Hungarian, Italian, Norwegian (Bokmål), Polish, Portuguese, Romanian, Russian, Slovak, Slovenian, Spanish, Swedish, Turkish, Croatian
Weight (kg)	5.30 kg
Size W x H x D (mm)	240 x 317 x 435
Calibration	Automated through Smart Cell
Operating Temperature	10°C - 40°C
Storage Humidity	15%-90% (non-condensing)
Warranty	1 year

MEDIA	
Materials Supported	Freezerbondz Polyester; Heat-shrink Polyolefin Sleeve; High Temperature Heat-shrink Polyvinylidene Fluoride Sleeve; Magnetic Polyester; Metal Detectable Polyester; Metallic, Non-metal Polyester; Metallised Polyester; Nylon Cloth; Paper; Phosphorescent Polyester; Polyester; Polyester Tag; Polyester with Polyester Overlaminated; Polyethylene Tag; Polyimide; Polyolefin; Polypropylene; Polyvinylfluoride; Reflective Tape; Self-laminating Polyester; Self-laminating Vinyl; StainerBondz Polyester; Tamper-evident Metallised Polyester; Thermoplastic Polyether Polyurethane; Vinyl; Vinyl Cloth
Label/Media Format	Media & Ribbon, supplied separately
Continuous vs Die-cut Labels	Continuous Tape & Die Cut Labels
Compatible Media	B30-, B30C-, B30EP-, B33-, B33C-, B33D-, B33FP-, B33FT-, B33R-
Number of stock	800+ standard parts
Max. Label Width (mm)	107.95
Min. Label Height (mm)	6.35
Min. Label Width (mm)	6.35
Max. Liner Width (mm)	107.95
Min. Liner Width (mm)	18
Max. Print Width (mm)	101.60
Recommended Usage per Day	1000

POWER SUPPLY	
Power Supply	AC Adaptor
Power Supply Voltage	110-240V

DISPLAY	
Display	Colour LCD Touchscreen
Display Resolution	272 x 480 px
On Screen Indicators	Supply Remaining, Ribbon Remaining, Ribbon and label part number recognition, WiFi, Ethernet Status, Error Messaging, Data Reception

SOFTWARE & CONNECTIVITY	
Connectivity Options	USB, Ethernet. Optional: WiFi (factory installed)
Software Compatibility	Brady Workstation, Windows based driver for 3rd party software use

FONTS/GRAPHICS/SYMBOLOLOGIES	
Built-in Fonts	Arial Courier New Times New Roman Trebuchet MS Verdana Tahoma
Bar Code Capability	Yes
Bar Code Type	Code 39, Code 93, Code 128 A, B, C, EAN-8, EAN-13, EAN/JAN 13, JAN-8, JAN-13, HIBC, Interleaved 2 of 5, Interleaved 2 of 5 w check digit, UPC A, Aztec, QR Code , datamatrix
Programming Language	BPL - scripting commands for sending scripts to the printer

COMPLIANCE	
Approval/Compliance	UL, cUL, CE, RoHS, RCM, KCC, EAC



Learn more about the BradyPrinter i3300 on : www.bradyeurope.com/i3300